

TMVJ

Rack mount cabinet with slide-out shelf

Description:

The **TMVJ** Fixed Cabinet introduces a compact, low cost solution for fiber optic cable termination. The **TMVJ** series is ideal for rack-mounting in confined areas such as equipment enclosures where rack space is limited. The cabinet is equipped with slide-out shelf with splice tray holder. This allows easy access to the splicing area for optical network reconfiguration during operation and prevents damage to fibers prior to routing into adapters. The modular system allows splicing and termination up to 96 fibers in rack height 1U.



*TMVJ-1U with FT-24-DSC
Base unit with patch panel for 24x DSC adapters*

Features:

- FTTH use - holder for minicables or microtubes
- Designed for cable or microtubes termination
- Compact robust design
- Slide-out shelf provides unrestricted access
- Changeable front panel, various adapters
- Coupling adapters mounted on the face panel
- Accommodates up to 96 fibers in 1 rack unit
- Durable powder coat finish
- Cable strain-relief and grounding provisions
- Accepts the industry's most common connector types
- Durable powder coat finish light grey colour (RAL 7038), optionally black colour (RAL 9005)
- Material-Aluminium alloy - low weight and shipment costs

Technical specifications:

PART NUMBER	FIBER CAPACITY		RACK UNITS	DIMENSIONS (HxWxD) mm	SHIP WGT (kg)
	FT-12-XX	FT-24-XX			
TMVJ – 1	12 (24) ¹	24 (48, 96) ¹	1	44 x 432 x 221	1.4

Note: 1) Fiber capacity is valid for SFF connector types, double capacity for duplex adapters (DLC, DSC, QLC)

Coupling panels FT series available for the common used connector adapter types in following configuration:

FT-12-XX 12 pcs ST, FC, SC, DSC, DLC, QLC, E2000, ... adapters
FT-24-XX 24 pcs ST, FC, SC, DSC, DLC, QLC, E2000, ... adapters


Applications:

- Rack-mount
- FTTH networks
- Customer premise remote cable drop

Product information and specifications:



TMVJ-1-24-DLCF S-C-2/PGR RAL 7038
Internal layout – DLC/PC patch panel and 2 splice cassettes



Empty **FT-24-DSC** front panel

Standard front panels:	
FT-12-DSC	12x duplex SC adaptors
FT-24-DSC	24x duplex SC adaptors
FT-12-SC	12x single SC adaptors
FT-24-SC line	24x single SC adaptors in-line
FT-24-SC zigzag	24x single SC adaptors zigzag
FT-12-ST(FC)	12x single ST (FC) adaptors
FT-24-ST(FC)	24x single ST (FC) adaptors

Ordering code:

TMVJ-X(B¹)	-	XX	-	XX(F)² X	-	CX / (PGx³) / (G⁴)
Version Rack Unit 1 1U		Fiber Capacity 1 ÷ 96 fibers		Coupling Type ST ST SC(F) SC FC FC E2(F) LSH (E2000) MJ MT-RJ DSC(F) Duplex SC DLC(F) Duplex LC QLC(F) Quadruplex LC Application M Multimode S Singlemode A APC		Splice Trays X: 0 ÷ 4

Note:

- 1) **B** - Black colour (RAL9005)
- 2) **F** - Fixed adaptors by screws
- 3) **PG** - Option for cable glands PG 13.5
x - R (right) or **L** (left) = only one PG on R or L side from the front view
- 4) **G** - Grounding option – protection grounding wires installed with grounding



Grounding accessories



Plastic cable gland PG 13.5



TMVJ-1B-24-DLC S-C-2 front view



TMVJ-1B-24-DLC S-C-2 rear view