

IGS-803SM

8x GbE RJ45 + 1x FE/GbE SFP + 2x FE/GbE/2.5G SFP



- UL60950-1, EN50121-4, NEMA-TS2, EN61000-6-2, EN61000-6-4, CE, FCC certified
- Supports IEEE 1588 PTP V2
- Supports u-Ring, ERPS, MSTP, RSTP, STP for redundant cabling
- Cable diagnostics, identifies opens/shorts distance



Ver.2022 Jul

These models are managed industrial grade GbE L2+ switches with 8 10/100/1000Base-T ports and 3 GbE/100M SFP ports (2 ports support 2.5GbE) that provide stable and reliable Ethernet transmission. Housed in rugged DIN rail or wall mountable enclosures, these switches are designed for harsh environments, such as industrial networking, security automation applications, intelligent transportation systems (ITS) and are also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications (See figure 1). Standard operating temperature range models (-10 to 60°C) and wide operating temperature range models (-40 to 75°C) fulfill the special needs of industrial automation applications.

Features

- Provides 5 instances that each can support μ -Ring, μ -Chain or Sub-Ring type for flexible uses. Supports up to 5 rings in one device (Please see CTC μ -Ring white paper for more details and more topology application)
 - μ -Ring for Redundant Cabling, recovery time < 10ms in 250 devices
 - Supports IEEE 1588 PTP V2 for precise time synchronization to operate in Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master, Slave mode by each port
 - Provides SmartConfig for quick and easy mass Configuration Tool*
 - Supports SmartView™ for Centralized Management*
- *Please see Chapter 1- [Software Management](#) for more details

Specifications

Standard	IEEE 802.3	10Base-T 10Mbit/s Ethernet	Console	RS-232 (RJ-45)								
	IEEE 802.3u	100Base-TX, 100Base-FX, Fast Ethernet	Network Cable	UTP/STP Cat. 5e cable or above EIA/TIA-568 100-ohm (100meter)								
	IEEE 802.3ab	1000Base-T Gbit/s Ethernet over twisted pair	Protocols	CSMA/CD								
	IEEE 802.3z	1000Base-X Gbit/s Ethernet over Fiber-Optic	Reverse Polarity Protection	Supported for power input								
	IEEE 802.3cb	2.5GBase-X	Overload Current Protection	Supported								
	IEEE 802.1d	STP (Spanning Tree Protocol)	CPU Watch Dog	Supported								
	IEEE 802.1w	RSTP (Rapid Spanning Tree Protocol)	Power Supply	Redundant Dual DC 12/24/48V (9.6~60VDC) Input power (Removable Terminal Block)								
	IEEE 802.1s	MSTP (Multiple Spanning Tree Protocol)	Power Consumption	<table border="1"> <thead> <tr> <th>Input Voltage</th> <th>12VDC</th> <th>24VDC</th> <th>48VDC</th> </tr> </thead> <tbody> <tr> <td>IGS-803SM</td> <td>8.6W</td> <td>10.8W</td> <td>11.5W</td> </tr> </tbody> </table>	Input Voltage	12VDC	24VDC	48VDC	IGS-803SM	8.6W	10.8W	11.5W
Input Voltage	12VDC	24VDC	48VDC									
IGS-803SM	8.6W	10.8W	11.5W									
	ITU-T G.8032 / Y.1344	ERPS (Ethernet Ring Protection Switching)	LED	Per unit: Power 1 (Green), Power 2 (Green), Fault (Amber), CPU Act (Green), Ring Master (Yellow) Per RJ-45 port: 10/100 Link/Active (Green) 1000 Link/Active (Amber) SFP Fiber Per port: Link/Active (Green)								
	IEEE 802.1Q	Virtual LANs (VLAN)	Jumbo Frame	9.6KB								
	IEEE 802.1X	Port based and MAC based Network Access Control, Authentication	IEEE 802.3ac	Max frame size extended to 1522Bytes (allow Q-tag in packet)								
	IEEE 802.3ac	Max frame size extended to 1522Bytes. Link aggregation for parallel links with LACP(Link Aggregation Control Protocol)	MAC Address Table	8K								
Standard	IEEE 802.3x	Flow control for Full Duplex	Memory Buffer	512K Bytes for packet buffer								
	IEEE 802.1ad	Stacked VLANs, Q-in-Q	Device Memory	16M Bytes Flash ROM, 128M Bytes RAM								
	IEEE 802.1p	LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization	Warning Message	System Syslog, SMTP/ e-mail event message, alarm relay								
	IEEE 802.1ab	Link Layer Discovery Protocol (LLDP)	Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC								
	IEEE 802.3az	EEE (Energy Efficient Ethernet)	Removable Terminal Block	Provide 2 redundant power, alarm relay contact, 6 Pin								
VLAN ID	4094	IEEE 802.1Q VLAN VID	Operating Temperature	-10 ~ 60°C (IGS-803SM) -40 ~ 75°C (IGS-803SM-E)								
Switch Architecture	Back-plane (Switching Fabric):	28Gbps Full wire-speed	Operating Humidity	5% to 95% (Non-condensing)								
Data Processing	Store and Forward											
Flow Control	IEEE 802.3x for full duplex mode	Back pressure for half duplex mode										
Network Connector	8x 10/100/1000Base-T RJ-45 + 1x FE/GbE SFP slot + 2x FE/GbE/2.5GbE SFP slot											
	RJ-45 UTP port support Auto negotiation speed, Auto MDI/MDI-X function, SFP port support dual speed with DDMI											

Storage Temperature	-40 ~ 85°C
Housing	Rugged Metal, IP30 Protection, Fanless
Dimensions	106 x 72 x 152 mm (D x W x H)
Weight	0.78kg
Installation Mounting	DIN Rail mounting, or wall mounting (optional)
MTBF	612,523 Hours (MIL-HDBK-217)
Warranty	5 years
Certification	
EMC	CE
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE EN55022 Class A
Railway Traffic	EN50121-4
Traffic control	NEMA TS2

Immunity for Heavy Industrial Environment	EN61000-6-2
Emission for Heavy Industrial Environment	EN61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (Burst) Level 3, Criteria A EN61000-4-5 (Surge) Level 3, Criteria B EN61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A
Safety	UL60950-1
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

Software Specifications

Topology	
VLAN	IEEE 802.1q VLAN, up to 4094 802.1Q VLAN VID IEEE 802.1q VLAN, up to 4094 Groups IEEE 802.1ad Q-in-Q MAC-based VLAN, up to 256 entries IP Subnet-based VLAN, up to 128 entries Protocol-based VLAN (Ethernet, SNAP, LLC), up to 128 entries VLAN Translation, up to 256 entries Private VLAN for port isolation GVRP (GARP VLAN Registration Protocol) MVR (Multicast VLAN Registration)
Link Aggregation (Port Trunk)	Static (Hash with SA, DA, IP, TCP/UDP port), up to 5 trunk group Dynamic (IEEE 802.3ad LACP), up to 5 trunk group
Spanning Tree	IEEE 802.1d STP IEEE 802.1w RSTP IEEE 802.1s MSTP
Multiple μ-Ring	up to 5 instances that each supports μ-Ring, μ-Chain or Sub-Ring type for flexible uses, and maximum up to 5 Rings. Recovery time <10ms The maximum number of devices allowed in a Ring supported ring is 250. (Please see CTC Union μ-Ring white paper for more details and more topology applications)
Loop Protection	Supported
ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection)	Recovery time <50ms Single Ring, Sub-Ring, Multiple ring topology network
QoS Features	
Class of Service	IEEE 802.1p 8 active priorities queues for per port
Traffic Classification QoS	IEEE 802.1p based CoS IP Precedence based CoS IP DSCP based CoS QCL(QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI QCE(QoS Control Entry): Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number
Bandwidth Control for Ingress	100~1,000,000 when the "Unit" is "kbps" and 1~1,000 when the "Unit" is "Mbps"
Bandwidth Control for Egress	100~1,000,000 when the "Unit" is "kbps" and 1~1,000 when the "Unit" is "Mbps" Per queue / Per port shaper
DiffServ (RF 2474) Remarkings	
Storm Control	for Unicast, Broadcast, Multicast
IP Multicasting Features	
IGMP / MLD Snooping	IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2 Port Filtering Profile Throttling, Fast Leave Maximum Multicast Group : up to 1022 entries Query / Static Router Port

Security Features	
IEEE 802.1X	Port-Based MAC-Based
ACL	Number of rules : up to 256 entries for L2 / L3 / L4 L2 : Mac address SA/DA/VLAN L3 : IP address SA/DA, Subnet L4: TCP/UDP
RADIUS authentication & accounting	
TACACS+ authentication & accounting, TACACS+ 3.0	
HTTPS, HTTP	Supported
SSL / SSH v2	Supported
User Name Password Authentication	Local Authentication Remote Authentication (via RADIUS / TACACS+)
Management Interface Access Filtering	Web, Telnet / SSH, CLI RS-232 console
Management Features	
CLI	Cisco® like CLI
Web Based Management	
Telnet	Server
SNMP	V1, V2c, V3
Modbus/TCP	Support for management and monitoring
SW & Configuration Upgrade	TFTP, HTTP Redundant firmware in case of upgrade failure
FTP client	Supports for upload/download configuration
RMON	RMON I (1, 2, 3, 9 group), RMON II
MIB	RFC1213 MIB II, Private MIB
UPnP	Supported
BOOTP	Supported
DHCP	Server, Client, Relay, Relay option 82, Snooping
RARP	Supported
IP Source Guard	Supported
Port Mirroring	Supported
Event Syslog	Syslog server (RFC3164)
Warning Message	System syslog, e-mail, alarm relay
DNS	Client, Proxy
IEEE 1588 PTP V2	Support 5 operating mode in each port : Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master, Slave
NTP, SNTP	Client
LLDP (IEEE 802.1ab)	Link Layer Discovery Protocol LLDP-MED
IPv6 Features	
IPv6 Management	Telnet Server/ICMP v6
SNMP over IPv6	Supported
HTTP over IPv6	Supported
SSH over IPv6	Supported
IPv6 Telnet	Supported
IPv6 NTP, SNTP	Client
IPv6 TFTP	Supported
IPv6 QoS	Supported

7


Industrial 1G/2.5G Managed Switch IGS-803SM

IPv6 ACL	Number of rules: up to 256 entries
	for L2 / L3 / L4
	L2 : Mac address SA/DA/VLAN
	L3: IP address SIP, Subnet (32bit)
	L4: TCP/UDP


Others Features	
Green Ethernet	Supports IEEE 802.3az EEE (Energy Efficient Ethernet) Management to optimize the power consumption
	Determine the cable length and lowering the power for ports with short cables
	Lower the power for a port when there is no link
Cable Diagnostic	LED Power Management :Adjustment LEDs intensity
	Measuring UTP cable normal or broken point distance

Application

Figure : Application Example



Dimensions



Ordering Information

Model Name	Total Port	UTP Port		Fiber Port		Power Input	Certification					Operating Temperature
		10/100/1000 Base-T	100/1000 Base-X	100/1000 Base-X	2.5G Base-X		Redundant	Railway EN50121-4	Traffic Control NEMA TS2	Safety UL60950-1	EN61000-6-2 EN61000-6-4	
IGS-803SM	11	8	1 SFP	2 SFP	2 SFP	12/24/48VDC	V	V	V	V	V	-10~60°C
IGS-803SM-E	11	8	1 SFP	2 SFP	2 SFP	12/24/48VDC	V	V	V	V	V	-40~75°C

Package List

- One device of the series
- Console cable (RJ-45 to DB9)
- Din Rail with screws
- Terminal block
- Protective caps for SFP ports

Optional Accessories

■ Wall Mount Kit

IND-WMK02 Wall Mount kit for Industrial product (Wide) (184 x 50mm)

■ Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with the series product for guaranteed compatibility and performance. The best performance can be guaranteed even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheet for more details and more items.)

ISFP-M7000-85-D(E) Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDMI, -10~70°C (-40~85°C)

ISFP-S7020-31-D(E) Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDMI, -10~70°C (-40~85°C)

ISFP-T7T00-00-(E) Industrial SFP 10/100/1000Base-T UTP 100meter, -10~70°C (-40~85°C)

ISFP-M5002-31-D(E) Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDMI, -10~70°C (-40~85°C)

ISFP-S5030-31-D(E) Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDMI, -10~70°C (-40~85°C)

■ Industrial Power Supply

MDR-20-24 Industrial Power, Input 85 ~ 264VAC/120 ~ 370VDC, Output 24VDC, 24W, -20 ~ +70°C

MDR-40-48 Industrial Power, Input 85 ~ 264VAC/120 ~ 370VDC, Output 48VDC, 40W, -20 ~ +70°C

■ Industrial Optical Fiber Bypass Switch

IBP-202 Optical Fiber Bypass Switch

7

Industrial 1G/2.5G Managed Switch IGS-803SM